

# CD-3301U/CD-3301UB



- Compact Gun Shape Light Weight Ergonomic Design for easy operation
- Designed to deliver quick scanning of 1D, 2D, QR Code on paper & Mobile devices
- Ideal for Retail, Document Processing, Back office, Courier Tracking
- Available in BT and Wired with optional stand

Specification	CD-3301U	CD-3301UB
Interface	Variant:1 USB	Variant:2 BLUETOOTH
Dimension	66 x 94 x 173	
Weight	143 (without battery)	203 (with battery)
Form Factor	Handheld 2D Barcode Scanner	
Light Source	White light LED	
Resolution	640 (H) x 480 (V) pixels	
Depth of Field	25-300mm @ EAN 13mil PCS=100%; 30-350mm @ QR 20mil PCS=100%	
Reading Pitch Angle	-55 to 0°, 0 to +55°	
Reading Skew Angle	-55 to 0°, 0 to +55°	
Scan Method	CMOS array sensor	
Scan Angle	Horizontal: 45°; Vertical: 34°	
Decode Capability	Decode Capability 1D: UPC/EAN/JAN,UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, SBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128,Code 93, Interleaved 2 of 5 (ITF),Addendum 2 of 5, IATA Code, MSI/Plessey, China Postal Code,Code 32 (Italian Pharmacode), RSS-14, RSS-Limited, RSS-Expand, etc. 2D: QR Code, Data Matrix, PDF417, Aztec, Maxicode, Dotcode, GS1 DataBar stack, etc.	
Min. Resolution	≥4mil	N/A
Input Voltage	5.0 +/- 0.5VDC	
Operating current	190mA	400mA max.
Operating temperature	-30°C to 60°C	
Storage temperature	-40°C to 70°C	
Ambient light	Direct Sun light: 0~100,000 lux max.	
Drop resistance	150 cm	
System Supported	Linux/Mac/Windows/Android	
Options	Scanner stand (STD-3200U)	
Operation Temp.	Temp : 0~50° Humidity : 20%~85%RH	

## Main Application Areas:



**POSIFLEX**

Certifications



V0.1\_18032025

## POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka 560093  
Tel : +91 80 4078 2700 | Mob : +91 9535432110  
Email : marketing@posiflexindia.com | www.posiflexindia.com

Authorized Distributor / Reseller