

Powerful yet Thrifty



PS-6216

Exceptional Value POS Terminal

Designed for both functionality and adaptability, the PS-6215/6216 is powered by Intel's TGL Core i Processor. It features an adjustable base, meeting the diverse needs of retailers and consumers alike. This affordable solution combines aesthetic appeal with a wealth of features.

PS-6216

Specification	PS-6216
Processor	Intel TGL Core i3 Intel TGL Core i5 Intel TGL Core i7
System Memory	DDR4 SO-DIMM x 2, max. 64GB
Storage Device	M.2 SSD [Support both SATAIII signal] x 1
TPM	Yes, TPM 2.0
Intel vPro Support	Yes, depends on CPU installed
OS Support	Windows 10 IoT LTSC / Windows 11 IoT LTSC

Display & Touch

LCD	15.6" TFT LCD with LED backlight
Resolution	1366 x 768
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)

I/O & Expansion

<u> </u>	
Serial Port	DB9 x 2 (on I/O plate) + RJ50 x 1 (on the top), $5V/12V$ support on all COM ports
Standard USB Port	USB 3.0 x 4 + USB 2.0 x 2 (on I/O plate) + USB 2.0 x 1 (on the top)
OTG USB	N/A
LAN Port	10/100/1000 Mb x 1
Display Port	HDMI x 1
CR Port	CR port x 1, control 2 x CR via optional Y-cable, support 24V CR
Audio	Internal 2W speaker x 1
Internal Expansion Slot	1 x M.2 2230 for Wi-Fi/BT

Physical Dimension

Dimensions (W x D x H in mm) 371.35 x 252	x 290.4
---	---------

Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

^{*}Please refer to the website for more attachment options.















V01.29.10.2024



POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

Authorized Distributor / Reseller

^{*}Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

^{*}The product information and specifications are subject to change without prior notice.