



Simplicity is the
Ultimate Sophistication

Cachet JK Series

27"/23.8" Modular Kiosk



HIGHLIGHTS

- 27"/23.8" true-flat PCAP touch screen
- Flexible configurations:
single / dual sided floor-standing, wall-mount
- Modular design for easy serviceability
- Reversible printing direction
- Popular uses: product display & advertising, ordering & payment, click & collect, ticketing & e-reservations, wayfinding & customer guidance



Windows/Android



NFC/RFID reader



2D scanner



Fingerprint sensor



Status Indicator



EMV Supportive*



PRODUCT SHOWCASE / Cachet JK-2700/2400 Series



Cachet JK-2400 Series

Specifications		JK-2410	JK-2432	JK-2452
Computer	Processor	Rockchip RK3399, Dual-core Cortex A72 up to 1.8GHz + Quad-core Cortex A53 up to 1.4GHz	Intel Elkhart Lake Celeron J6412, up to 2.60 GHz, 1.5M Cache	Intel Tiger Lake UP3 Core i3 Intel Tiger Lake UP3 Core i5 Intel Tiger Lake UP3 Core i7
	System Memory	DDR4 4 GB	DDR4 SO-DIMM x 1, max 16GB	DDR4 SO-DIMM slot x 1, max. 32 GB
	Storage Device	32 GB eMMC + microSD slot x 1	M.2 SSD [SATA Signal Only] x 1	
	Intel vPro Support	N/A	N/A	Yes, depend on processor
	TPM Support	N/A	TPM 2.0	
	Power Supply	12V/60W x 1+ 24V/60W x 1	12V/84W x 1 + 24V/60W x 1	
	OS Support	Android 9.0*/Android 10.0 with GMS	Windows 10 IoT 64 bit/ Windows 11	
	Serial Port	2, RJ50 x 2, 5V/12V support on all COM ports	3, DB9 x 1 + RJ50 x 2, 5V/12V support on all COM ports	
	Standard USB Port	6, USB 3.0 x 1 + USB 2.0 x 5	8, USB 3.0 x 2 + USB 2.0 x 6	8, USB 3.0 x 4 + USB 2.0 x 4
	OTG USB	Micro-USB x 1	N/A	
	Display Port	HDMI x 1	HDMI x 1	
	LAN Port	10/100 Mb x 1; 10/100/1000 Mb x 1	10/100/1000 Mb x 2	
	Audio	Internal 3W speaker x 2	Internal 3W speaker x 2	
Internal Expansion Slot	N/A	M.2 x 1		
Display & Touch	LCD	23.8"		
	Resolution	1920 x 1080		
	Touch	True-flat PCAP touch with multi-touch support		
Physical Dimension	Dimension (W x D x H in mm)	602 x 602 x 1740 (Single or dual sided); 400 x 140 x 988 (Wall-mounted)		
	Weight (N. W. in kg)	48.8 (Single sided); 60.8 (Dual sided); 20.5 (Wall-mounted)		
Environmental	Operating Condition	0°C - 40°C, 20%RH - 90%RH		
	Storage Condition	-20°C - 70°C, 10%RH - 90%RH		
Standard Components	Status Indicator	RGB Color LED indicator		
	Proximity Sensor	Range from 45cm ~ 80cm (for dark color objectives); Range from 45cm ~ 150cm (for light color objectives)		
	Camera	1MP wide angle camera		
	Printer	3" thermal printer w/ auto cutter, 250 mm/sec (max.)		
Optional Components	WiFi	USB dongle (cannot coexist with 4G/LTE)		
	Scanner	2D barcode scanner		
	EMV Payment Device Bracket Support*	Custom bracket support for various EMV payment devices		
	MSR	3 tracks ISO or JISII (HID/VCOM selection)		
	Fingerprint Sensor	Optical type		
	NFC/RFID Reader	Support ISO/IEC 14443-A&B (MIFARE), JIS x 6319-4 (Felica), ISO/IEC 15693, NFC protocols - tag read/write (ISO/IEC-18092)		
	4G/LTE Communication	Support selected bands & countries with full SIM slot (mini-PCIe module) by request (cannot coexist with WIFI)		

*Google Play services is not supported by this device. *Designed and Manufactured in Taiwan by Posiflex Technology, Inc. *Posiflex does not sell the EMV payment devices, but can provide bracket support with an additional charge.

*The product information and specifications are subject to change without prior notice.

Cachet JK-2700 Series

Specifications		JK-2710	JK-2752
Computer	Processor	Rockchip RK3399, Dual-core Cortex A72 up to 1.8GHz + Quad-core Cortex A53 up to 1.4GHz	Intel Tiger Lake UP3 Core i3 Intel Tiger Lake UP3 Core i5 Intel Tiger Lake UP3 Core i7
	System Memory	DDR4 4 GB	DDR4 SO-DIMM slot x 1, max. 32 GB
	Storage Device	32 GB eMMC + microSD slot x 1	M.2 SSD [SATA Signal Only] x 1
	Intel vPro Support	N/A	Yes, depend on processor
	TPM Support	N/A	TPM 2.0
	Power Supply	12V/60W x 1+ 24V/60W x 1	12V/84W x 1 + 24V/60W x 1
	OS Support	Android 9.0*/Android 10.0 with GMS	Windows 10 IoT 64 bit/ Windows 11
	Serial Port	2, RJ50 x 2, 5V/12V support on all COM ports	3, DB9 x 1 + RJ50 x 2, 5V/12V support on all COM ports
	Standard USB Port	6, USB 3.0 x 1 + USB 2.0 x 5	8, USB 3.0 x 4 + USB 2.0 x 4
	OTG USB	Micro-USB x 1	N/A
	Display Port	HDMI x 1	HDMI x 1
	LAN Port	10/100 Mb x 1; 10/100/1000 Mb x 1	10/100/1000 Mb x 2
	Audio	Internal 3W speaker x 2	Internal 3W speaker x 2
	Internal Expansion Slot	N/A	M.2 x 1
Display & Touch	LCD	27"	
	Resolution	1920 x 1080	
	Touch	True-flat PCAP touch with multi-touch support	
Physical Dimension	Dimension (W x D x H in mm)	602 x 602 x 1800 (Single or dual sided); 424 x 140 x 1050 (Wall-mounted)	
	Weight (N. W. in kg)	50.3 (Single sided); 63.8 (Dual sided); 22 (Wall-mounted)	
Environmental	Operating Condition	0°C - 40°C, 20%RH - 90%RH	
	Storage Condition	-20°C - 70°C, 10%RH - 90%RH	
Standard Components	Status Indicator	RGB Color LED indicator	
	Proximity Sensor	Range from 45cm ~ 80cm (for dark color objectives); Range from 45cm ~ 150cm (for light color objectives)	
	Camera	1MP wide angle camera	
	Printer	3" thermal printer w/ auto cutter, 250 mm/sec (max.)	
Optional Components	WiFi	USB dongle (cannot coexist with 4G/LTE)	
	Scanner	2D barcode scanner	
	EMV Payment Device Bracket Support*	Custom bracket support for various EMV payment devices	
	MSR	3 tracks ISO or JISII (HID/VCOM selection)	
	Fingerprint Sensor	Optical type	
	NFC/RFID Reader	Support ISO/IEC 14443-A&B (MIFARE), JIS x 6319-4 (Felica), ISO/IEC 15693, NFC protocols - tag read/write (ISO/IEC-18092)	
4G/LTE Communication	Support selected bands & countries with full SIM slot (mini-PCIe module) by request (cannot coexist with WiFi)		

Google Play services is not supported by this device. Designed and Manufactured in Taiwan by Posiflex Technology, Inc. *Posiflex does not sell the EMV payment devices, but can provide bracket support with an additional charge.

The product information and specifications are subject to change without prior notice. Product specifications and model configurations are subject to change and may vary by global region.



POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.
 #7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd,
 Nagavarapalya, Bengaluru, Karnataka 560093
 Tel : +91 80 4078 2700 | Mob : +91 9535432110
 Email : marketing@posiflexindia.com | www.posiflexindia.com

Certifications



EN20240315V4

Authorized Distributor / Reseller