



LM-3210E

- Support All XT Series (excl. XT-2614Q) & 12.1" KS Series
- 9.7" LCD 2nd monitor bezel-free display

Specification	LM-3210E
LCD	9.7" TFT LCD
Resolution	Up to 1024 x 768
Active Area	196.61 (H) x 147.46 (V)
Pixel Pitch	0.192 (H) x 0.192 (V)
Pixel Arrangement	RGB Vertical Stripe
Viewing Angle	60/70/70/70 (U/D/L/R)
Contrast Ratio	500:1
Response Time	20 ms (Raising + Falling)
Brightness	350 cd/m ²
Interface	VGA
Power Supply	12V from Posiflex terminal VGA port
System Supported	All XT Series (excl. XT-2614Q) & 12.1" KS Series
Programmability	
Code Type	Keyboard scan codes
Contents Length	1 - 255 byte(s)/key
Coverage	English or European, software configured

Language	5VDC +/- 10%
Environmental	
Shock	10 to 90 %; 5 to 90 % non-condensing
Humidity	0°C to 50°C
Operation Temp.	-20°C to 70°C
Storage Temp.	15,000,000 strokes/min

Design and Manufacturing in Taiwan by Posiflex Technology, Inc.
The product information and specifications are subject to change without prior notice.
Please refer to the web site for more attachment options.

Certifications		V1.1_17042021
----------------	--	---------------

Authorized Distributor / Reseller
