

PC-2111E-G2

Specification	PC-2111E-G2
Processor	Intel Elkhart Lake Celeron J6412
System Memory	1x DDR4 SO DIMM, max. 16GB
Storage Device	1 x M.2 2280
TPM	TPM 2.0
Power Supply	12V/60W
OS Support	Windows 10 IoT LTSC Windows 11 IoT LTSC

Display & Touch

LCD	10.1" TFT LCD with LED backlight
Resolution	1280 x 800
Touch	PCAP supporting multi-touch

I/O & Expansion

Serial Port	RJ-50 x 1
Standard USB Port	4 x USB 3.0
LAN Port	1 x 10 / 100 / 1000 Mb
Display Port	1 x mini-HDMI
CR Port	1, control 2 x CR, support 24V
Audio	1 x internal speaker
LED Indicator	1 x bi-color LED
Expansion Slot	1 x M.2 2230 for WiFi/BT

Physical Dimension

Dimensions (W x H x D in mm)	259 x 192.8 x 200.7
Weight (N. W. in kg)	1.96kg (With base stand)

Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

Attachment Options

Attachment	TA-220-PC, TA-620-PC
Base	N/A

Extraordinary Within



PC-2111E-G2

10.1" Panel PC

*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.
*The product information and specifications are subject to change without prior notice.
*Please refer to the website for more attachment options.

Certifications



EN20240416V4

Authorized Distributor / Reseller

POSIFLEX

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavapalya, Bengaluru, Karnataka 560093
Tel: +91 80 4078 2700 | Mob: +91 9535432110
Email: marketing@posiflexindia.com | www.posiflexindia.com

POSIFLEX