



## TM-5015

- Slim and sturdy design
- Seamlessly align with the fashionable style of the Gen9 base
- Durable housing for long-lasting performance
- Support optional attachments including MSR, RFID, a fingerprint sensor, and iButton
- Integrated 2D barcode scanner
- Keep counter space tidy and organized

Specification	TM-5015
LCD	15" TFT LCD
Active Area	304.1 (H) x 228.1 (V)
Pixel Pitch	0.297(H) x 0.297(W)
Pixel Arrangement	RGB Vertical Stripe
Viewing Angle	88/88/88 degree (U/D/L/R)
Contrast Ratio	2500:1
Response Time	16 ms (Raising)/7 ms (Falling)
Brightness	350 nits
Resolution	1024 x 768
Interface	VGA+HDMI+DP

Design and Manufacturing in Taiwan by Posiflex Technology, Inc.
The product information and specifications are subject to change without prior notice.
Please refer to the web site for more attachment options.

Certifications













V1.1 1704202





Power Supply	12V from Gen9 base power board or VGA (from Posiflex terminal)
System Supported	Gen9 base
Shock	Yes (75 and 100)
Humidity	MSR; iButton; 2D Scanner; 1MP camera; NFC/RFID; Fingerprint
Operation Temp.	0°C - 40°C, 20%RH - 90%RH
Touch@Touch Type	Bezel-free PCAP touch
Touch@interface	USB 2.0 from Posiflex terminal

Design and Manufacturing in Taiwan by Posiflex Technology, Inc.
The product information and specifications are subject to change without prior notice.
Please refer to the web site for more attachment options.













