

## Your Versatile Partner



# TX-2300-G2

## Multi-Purpose Control Box

The TX-2300-G2 Series is a multi-purpose control box that runs on an Intel Elkhart Lake dual core CPU. It offers a vast range of I/O connectivity options including HDMI ports x 2 to connect POS peripherals, and can be used as a full fledge POS Box, a Kitchen Display System (KDS), a digital signage controller or any industrialized applications.

## TX-2300-G2

#### Compact and Flexible

The small footprint and VESA mounting points of the TX-2300-G2 Series allow easy installation in anywhere you need a Point-of-Service system.

#### Patented Fanless Technology

Fanless design boasts anti-dust and silent operation advantages to meet the requirements of harsh and quiet environments, respectively.

### Expandable and Configurable

Connect to a series of POS peripherals and options for greater productivity and flexibility to fit in your store environment.

| Specification | TX-2300-G2 |
|---------------|------------|
|---------------|------------|

| Opodinication               |  |  |
|-----------------------------|--|--|
| Processor                   | Intel Elkhart Lake Celeron J6412, up to 2.60 GHz, 1.5M Cache<br>Intel Elkhart Lake Celeron N6210, up to 2.60 GHz, 1.5M Cache |  |
| System Memory               | DDR4 SO-DIMM x 2, max. 32GB  |  |
| Storage Device              | M.2 connector [supporting AHCI mode] x 1   |  |
| RAID Function               | N/A  |  |
| Intel vPro Support          | N/A  |  |
| TPM                         | Yes, TPM 2.0   |  |
| Power Supply                | 12V/60W  |  |
| OS support                  | Windows 10 loT 64 bit/ Windows 11  |  |
| I/O & Expansion             |  |  |
| Serial Port                 | 4, DB9 x 2 + RJ50 x 2, 5V/12V<br>support on all COM ports  |  |
| Parallel Port               | 1, via optional cable from service window  |  |
| Standard USB Port           | 6, USB 3.0 x 2 + USB 2.0 x 4   |  |
| PoweredUSB Port             | N/A  |  |
| LAN Port                    | 10/100/1000 Mb x 1   |  |
| Display Port                | VGA x 1 (12V support for Posiflex monitors) + HDMI x 2   |  |
| CR Port                     | 1, control 2 CR via optional Y-cable   |  |
| PS/2 Port                   | Yes  |  |
| Audio                       | Internal 2W speaker x 1 + Mic-in/Line-out  |  |
| Expansion Slot              | M.2 slot x 1   |  |
| Physical Dimension          |  |  |
| Dimension (W x D x H in mm) | 220 x 202 x 56   |  |
| Weight (N. W. in kg)        | 1.2  |  |
| Environmental               |  |  |
| Operating Condition         | 0°C - 40°C, 20%RH - 90%RH  |  |
| Storage Condition           | -20°C - 70°C, 10%RH - 90%RH  |  |
| Built-in Options            |  |  |
| WiFi                        | M.2 WiFi/BT module   |  |





















#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka - 560093 Tel: +91 80 4078 2700 | Mob: +91 9535432110

Email: marketing@posiflexindia.com | www.posiflexindia.com

Authorized Distributor / Reseller



 $<sup>^\</sup>star \mbox{Designed}$  and Manufactured in Taiwan by Posiflex Technology, Inc.

<sup>\*</sup>The product information and specifications are subject to change without prior notice.
\*Please refer to the website for more attachment options.