

# WT1010A G2

Specification	WT1010A G2
Processor	Intel Elkhart Lake Celeron J6412
System Memory	1 x DDR4 SO-DIMM socket, max. 16GB
Storage Device	M.2 connector x 1 [SATA Signal Only]
TPM	TPM 2.0
Power Supply	12V/40W
OS Support	Windows 10 IoT LTSC Windows 11 IoT LTSC

## Display & Touch

LCD	10.1" TFT LCD with LED backlight
Resolution	1280 x 800
Touch	PCAP supporting multi-touch

## I/O & Expansion

Serial Port	N/A
Standard USB Port	4 x USB 3.0
LAN Port	1 x 10 / 100 / 1000 Mb
Display Port	N/A
CR Port	N/A
Audio	1 x internal speaker
LED Indicator	1 x bi-color LED
Expansion Slot	1 x M.2 2230 for WiFi/BT

## Physical Dimension

Dimensions (W x H x D in mm)	259 x 172.6 x 36.5
Weight (N. W. in kg)	1.01kg

## Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

## Attachment Options

Attachment	WT1010A G2
Base	WT1010A G2 Stand

Extraordinary Within



# WT1010A G2

10.1" Panel PC

\*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.  
\*The product information and specifications are subject to change without prior notice.  
\*Please refer to the website for more attachment options.

Certifications



EN20240416V3

**POSIFLEX**

**POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.**

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavapalya, Bengaluru, Karnataka 560093  
Tel : +91 80 4078 2700 | Mob : +91 9535432110  
Email : marketing@posiflexindia.com | www.posiflexindia.com

